



# WESSEX INTUMESCENT SUPPLIES LTD

Unit 22, Regent Trade Park, Barwell Lane, Gosport, Hants. PO13 0EQ

Fire, Draught, Weather & Acoustic Seals  
Conservatory Roof Glazing Systems

Tel: 01329 221111 Fax: 01329 221122

Email: sales@wis-ltd.com

Website: www.wis-ltd.com

## Dry Glazing Tapes

Specially designed self-adhesive dry glazing tapes, extruded from closed cell EPDM, the profiles allow for ease of compression whilst the aggressive adhesive ensures a fast and simple application.

### Benefits

- Quick & easy installation – no mechanical fixings are required
- Closed cells and continuous skin
- Reinforcement scrim to ensure tape doesn't stretch
- Excellent resistance to cold, heat and ageing



**Availability:** 9mm x 3mm, 10mm x 5mm & LS Profile 12mm x 3mm

**Colour:** Black

### Application Instructions:

All surfaces must be clean, dry and free from all contaminants ie. grease, silicones, dust and the air temperature and bonding items (tape, beads, glass) are above 10°C prior to application.

Position tape on glazing rebate and bead so that the tape edge is aligned flush with the sight line. Initial adhesion is obtained by applying firm, uniform pressure to the tape during application. Tape on horizontal rebate should run past the verticals, the tape should be cut by knife cut and butted closely together at corners without overlapping.

The tape should be used under 20% compression for optimum adhesive performance and to provide an effective weather seal. Setting blocks are recommended for all window and door systems. Position setting blocks on bottom rail as required. Finally fix external beads into position ensuring tape is compressed.