



WESSEX INTUMESCENT SUPPLIES LTD

Unit 22, Regent Trade Park, Barwell Lane, Gosport, Hants. PO13 0EQ

Fire, Draught, Weather & Acoustic Seals
Conservatory Roof Glazing Systems

Tel: 01329 221111 Fax: 01329 221122

Email: sales@wis-ltd.com

Website: www.wis-ltd.com

Georgian Bar Tape

A high performance double sided self-adhesive polyethylene foam tape specifically designed for bonding glazing bars to the surface of glass units offering good UV resistance, aggressive adhesive bond and good dynamic shear properties.

Benefits

- Quick & easy installation – no mechanical fixings are required
- Immediate bonding – saves time as no curing or drying time is required
- Reliable bonding for internal and external applications
- Service Temperature -40°C to +70°C



Availability: White or Black

Thicknesses: 1mm & 2mm

Standard widths: 18mm, 20mm & 22mm *(other widths available to order).*

Application Instructions:

All surfaces must be clean, dry and free from all contaminants ie. grease, silicones, dust and the air temperature and bonding items (tape, bars, glass) are above 10°C prior to application.

Use Isopropanol or similar cleaner to ensure clean contact surfaces.

Apply tape to back of bars using even pressure over the full length/width. *(the bars may require sealing prior to application of tape to ensure satisfactory adhesion)*

Position bar on glass and once in correct position apply even pressure along full length of bar to ensure good bond, full bond strength may take several hours to develop depending on temperature.

Like all self-adhesive products the tape requires smooth clean surfaces and firm pressure for best results